

INSTANTANEOUS MULTI-POINT WATER HEATER



- 28kW heat output
- 11.8 Lt/min flow rate (35°C temperature rise)
- Simplified installation and commissioning
- Fully modulating gas valve to accurately match output to demand
- Electronic NTC sensing for accurate and stable temperature control
- Electronic ignition - no energy wasteful pilot light or constantly running fan
- 1.3m built in flying electrical lead
- Versatile concentric or twin flue option available
- Simple servicing - No diaphragm or water section reducing maintenance requirements
- Backed up by Vokera's industry leading service and technical support

	Units	AquaNova
Heat Output	kW	28.8
DHW Flow Rate (35°C Rise)	Lt/min	11.8
Maximum flue length		
Horizontal (Ø100mm)	m	2.4
Vertical (Ø100mm)	m	3.8
Twin (Ø80mm)	m	6/6*
Height (ex. flue elbow)	mm	640
Width	mm	400
Depth	mm	246
Connections		
Cold Water Inlet	mm	15
DHW Outlet	mm	15
Gas	mm	15

* plus flue terminal

Vokera Ltd.
4th Floor,
Catherine House,
Boundary Way,
Hemel Hempstead. HP2 7RP
Tel: 0870 333 0520
Fax: 01442 281460