





models available with choice of 12kW, 16kW or √ heat output

mplified installation and commissioning

All major system components built-in - pump, expansion vessel, safety valve, automatic air vent, automatic by-pass - saving space, installation time and material

Simple servicing with all components in one place

 For use with sealed central heating system, no need for feed and expansion tank dry loft possible

Optional built-in programmers available

Compact dimensions with attractive Italian designed casing

Versatile concentric and twin flue options available

Built-in anti-cycling control

 Easily linked to other Vokèra boilers for larger output modular applications

Backed up by Vokèra's industry leading service and technical support

16e

20e

| | | MYNUTE |
|------|------------------|-------------------|
| | | • SEDBUK Ba |
| | | • Three m 20kW |
| | | • Sim |
| | | • |
| | - | |
| * 11 | Med Py ◆ | 2 |
| | | |
| | • 4 | |
| | | 4 6 6 6 |
| | ~ duma | |
| | | |
| | | |
| | | |
| | T and the second | |

| Heat Output | kW | 12.0 | 16.0 | 20.0 |
|---|----------------|----------------------|----------------------|----------------------|
| SEDBUK Efficiency | % | 78.0 | <i>7</i> 8.0 | 78.0 |
| Maximum Flue Length Horizontal (Ø100mm) Vertical (Ø100mm) Twin (Ø80mm) | m m m | 4.5 5.5 14/14* | 3.4 4.4 14/14* | 3.4 4.4 14/14* |
| Height (ex. flue elbow) Width Depth | mm mm mm | 740 366 315 | 740 366 315 | 740 366 315 |
| Connections Flow and Return Safety Valve | mm mm | 22 15 | 22 15 | 22 15 |

Units

Hemel Hempstead. HP2 7RP Tel: 0870 3330520 Fax: 01442 281460

Vokèra Ltd. 4th Floor, Catherine House, Boundary Way,

plus flue terminal