

HIGH EFFICIENCY CONDENSING SYSTEM BOILER



- SEDBUK Band A
- Available in 16kW and 26kW outputs with full air/gas modulation to accurately match output to demand
- Pre-mix combustion minimises emissions of harmful greenhouse gases - NO_x and CO₂
- All major system components built-in - pump, expansion vessel, automatic air vent, automatic by-pass - saving space, installation time and material
- Simple servicing with all components in one place
- For use with sealed central heating system, no need for feed and expansion tank - dry loft possible
- Versatile concentric and twin flue options available
- Many built-in features:
 - Anti-cycling control
 - Filling loop
 - Frost protection
 - Automatic by-pass
 - Self diagnostic fault finding
 - Automatic pump spin
- Easily linked to other Vokèra boilers for larger output modular applications
- Backed up by Vokèra's industry leading service and technical support

Vokèra Ltd.
4th Floor,
Catherine House,
Boundary Way,
Hemel Hempstead. HP2 7RP
Tel: 0870 3330520
Fax: 01442 281460

	Units	Pinnacle 16	Pinnacle 26	
Heat Output - CH (80°/60°)	kW	15.4	25.3	
	- CH (50°/30°)	kW	16.8	26.8
SEDBUK Efficiency	%	90.1	90.4	
Maximum Flue Length	Horizontal (Ø100mm)	m	10.0	6.45
	Vertical (Ø100mm)	m	11.0	7.45
	Twin (Ø80mm)	m	39/39*	29/29*
Height (ex. flue elbow)	mm	820		
Width	mm	450		
Depth	mm	355		
Connections				
Flow and Return	mm	22		
Safety Valve	mm	15		
Gas	mm	15		
Condensate	mm	21.5		

* plus flue terminal